

# The KEK Proton Synchrotron

Masahito YOSHII

National Laboratory for High Energy Physics, KEK  
1 - 1 OHO, TSUKUBA - SHI IBARAKI - KEN, 305 JAPAN

## Abstract

The KEK Proton Synchrotron has been operated successfully to serve intense proton beams for the particle and nuclear physics experiments for the past two decades. In recent years, the large efforts for improving the extracted beam quality and the beam transfer efficiency between each cascaded accelerator have been done. Deuteron beam has been successfully accelerated in 1992. Moreover, ion beam acceleration has been initiated recently. As a next step, helium beam acceleration is scheduled in April 1994.

## I. INTRODUCTION

The KEK Proton Synchrotron is an accelerator complex consisting four accelerators: 750 keV Cockcroft Walton, 40 MeV Linac, 500MeV Booster Synchrotron and 12 GeV Main Ring. Since the Proton Synchrotron made a start on its 12 GeV operation in Dec. 1976, the accelerator has been repeatedly upgrading in order to increase its proton beam intensity. However, our recent efforts have rather directed for improving the extracted beam quality and the beam transfer efficiency between each cascaded accelerator. For this purpose, a new computer control system with the distributed VME computers have been introduced to the KEK-PS, which aimed to have effective and systematic controls and data handling of each component of the machine [1]. Lots of signals related to the accelerator operation also send to the computers, and their on-line analysis become to be efficiently available.

The Main Ring Synchrotron has been utilized mainly to produce secondary beams, such as anti-proton, kaon, pion, and so on, for the past two decades. However, coming into the 1990's, the experimental programs using primary beams have been proposed. And the KEK Proton Synchrotron has been required for the machine available for accelerating and extracting not only proton beams but various beams, such as deuteron, He and so on, with various energies. For the sake of realizing such requirements, modifications of the accelerators have been initiated as a task in the Accelerator Division.

In Jan.1992 deuteron beam was successfully accelerated at KEK, and the experimental programs have been successfully carried out in 1992 and 1993. Since 1991, one month of coming every April has been assigned to accelerate deuterons. Helium beam acceleration is scheduled in April 1994 as a next step of atomic beam programs.

## II. RECENT PROTON ACCELERATION

One of the most effective and practical improvements for stable acceleration is that by moving the low level electronics of the booster rf system to the auxiliary room the booster rf systems are less affected from the beam induced noises, which also makes possible to optimize precisely the loop gains for the rf feedbacks.

In the last two years, the annual operation is about 4500 hours, ~67% of total operation time spent for physics programs in which deuteron programs were included and ~17% for accelerator studies.





Figure 1. Cycle-to-Cycle Variation of Average Beam Intensity of both The Booster and 12-GeV Proton Synchrotrons.

### A. Preinjector and Injector

As Figure 2 shows, fluctuations in an intensity of extracted beam from the 12 GeV Main Ring is closely related to a change of beam current from the ion source. This change of beam current is due to some conditions inside the ion source, such as a change of cathode current, a change of amount of Cesium ions on the converter surface, etc.



(unit: 1 day / bin)

Figure 2. Fluctuations in Both The Extracted and Ion Source Beam Intensities

And also, a discharge inside the accelerating tube of the Cockcroft-Walton preinjector affects the beam intensity.



to ~ 5 kV. Under this condition, the bunch length of the beam injected into the Main Ring is typically 160 nsec. The pulse widths of both the booster extraction and the main ring injection kicker magnets are 130 and 110 nsec in proton acceleration. For deuteron acceleration, therefore, those widths are extended to be 250 and 180 nsec, respectively, so that the kickers cannot kick the edge of beam.

## IV. HELIUM BEAM ACCELERATION

In the case of acceleration of atomic ions heavier than deuterium ion such as  $^4\text{He}$ ,  $^{12}\text{C}$ ,  $^{14}\text{N}$ ..., not negatively but positively charged ions are accelerated in the present Linac, hence the booster injection method entirely differs from that in proton ( $\text{H}^-$ ) or deuteron ( $\text{D}^-$ ). A multi-turn injection technique is adopted instead of a conventional charge exchange injection method. A new septum magnet [5] has been invented so that both negative and positive beams could be injected into the Booster Synchrotron. This magnet is indeed a key whether ion beam acceleration becomes possible without disturbing acceleration of a high intensity proton beam supplied to the Booster Utility Facility.




Figure.2 Comparison of Booster Injections for Negative and Positive Ions

### A. Booster Injection

The newly designed septum magnet is replaced with one of four bump magnets (named as Bump II in Figure 2). This septum magnet has the opposite sign magnetic fields in both sides of its vertical septum plane. So, negatively charged beam such as  $\text{H}^-$  or  $\text{D}^-$  travels outside of the septum plane, and its electrons are stripped at a carbon foil. On the other hand, in the case of a positively charged beam injection, the closed orbit at the injection point is shifted about 50 mm outside from the central orbit by exciting two fast bump magnets, which are placed at both up- and down- streams of the booster injection point (not shown in Figure 2), the beam is injected inside of the septum plane and its injection point moves horizontally from the center to the outside of the phase space by moving the bump orbit.

### B. Helium Acceleration

Helium ions are extracted as singly charged positive ions from an cusp type of ion source, and accelerated by the

Cockcroft Walton preinjector with total accelerating voltages of 750 kV, at an adjacent gas cell ( $\text{N}_2$  or Ar gas) their electrons are stripped and fully stripped helium ions;  $\text{He}^{2+}$  ( $e/m = 0.5$ ), are generated. They are injected into the Linac and accelerated up to 10 MeV/u. The capture efficiency is expected to be ~30%, that is comparative with that in deuteron acceleration. The beam intensity in the Booster Synchrotron should be less than a tenth of that in deuteron acceleration, because of the 3 to 6 turns of injection are expected. In Table-2, the estimated helium beam intensities at each point of acceleration are summarized.

Table 2  
Summary of Expected Helium Beam Intensity

Ion Source	15 pmA
after gas stripper : $\text{He}^{2+}$	5 pmA
Linac : Entrance	3 pmA
: Exit	0.9 pmA
Booster	$3 \times 10^{10}$ ppb *
Main Ring	$2 \times 10^{11}$ ppp **

\* : estimation of three turns injection including 30% of beam losses in the ring

\*\* : 9 bunches and 30% of beam losses in the ring

## V. SUMMARY

In the 1990's, the KEK Proton Synchrotron has attained a steadied age. Our efforts have been focused on operating each component of the accelerators stable and systematic. The introduction of distributed VME computer system is also one of the factors met with a good result. On the other hand, the experiment programs using primary beams have been accepted at the Program Advisory Committee. And, both accelerations of various ions, including protons, and their extractions with various energies have been strongly required of the accelerator. Deuteron program was the really first step toward the new future of the KEK Proton Synchrotron. To succeed to accelerate helium acceleration in the next step is to develop the KEK Proton Synchrotron into the world unique accelerator, which may cover both particle and nuclear physics in the region of energy of GeV per nucleon.

The author thanks all members of the PS group for useful discussions and their encouragement.

## VI. REFERENCES

- [1] T.Katoh, et al., "VME-Computer Based Control System for The KEK Proton Synchrotron", KEK-Preprint 87-91
- [2] T.Kawakubo, et al., "Fast Data Acquisition System of A Non-Destructive Profile Monitor for A Synchrotron Beam by Using A Microchannel Plate with Multi-Anodes", Nucl.Instr.and Meth. A302,1991, pp.397-405.
- [3] K.B.Unser, CERN SL/91-42(B1)
- [4] Y.Mori, et al., "Acceleration of Deuteron Beam in the KEK Proton Synchrotron", IEEE Acc. Conf.93, to be published
- [5] "The PS Collider Design Report 2", KEK Report 90-13